

## SPECIFICATIONS

		1026R
		1R SERIES
<b>ENGINE</b>		
Type		3-Cylinder Diesel
ECE-R120 Net bare engine power at rated engine rpm kW (hp)		18.5 (24.8) at 3,200
Rated PTO kW (hp)		13.4 (18)
Displacement, ltr		1.115
Max Torque, Nm		63.7
Air Cleaner		Dry Type w/ Safety Element
Fuel Tank Capacity, ltr		21.2
<b>DRIVETRAIN</b>		
Transmission – Gear		N/A
Transmission – Hydro		2 range Hydro / Two Pedal Automatic
Max. Speed*, km/h (mph)		14.5 (9.0)
Clutch PowrReverser™		N/A
Brakes		Wet Disc
Steering		Power Steering
Differential Lock		Standard
4-Wheel Drive		Standard
<b>HYDRAULIC SYSTEM</b>		
Type		Open Centre
Total Flow, l/min		24
Implement, l/min		13.2
Steering, l/min		10.8
<b>HITCH</b>		
Category 1 Rear 3pt Hitch		Standard
Lift Capacity at Lift Points, kg		525
Lift Capacity 610 mm (24 in) Behind Lift Ends, kg		309
<b>PTO</b>		
Type		Independent
Location		Standard Rear, Mid Standard and Front Optional
Speed		540 Rear
Rotation		210°CCW Mid and Front
Clutch / Brake		Wet Multi Disc
<b>SAFETY</b>		
ROPS / Cab		Complies with EU 1322/2014 and OECD
Driver Safety System		
– PTO Brake		Standard
– Operator Present		Standard
<b>DIMENSIONS</b>		
Total Length with 3pt Hitch, mm		2,846
Total Width, mm		1,200
Wheelbase, mm		1,450
Height with ROPS, mm		2,280
Height with Cab, mm		1,985
Weight Empty with ROPS / with Cab, kg		700 / 850
Total Permissible Weight, kg		1,327
Front Axle, kg		612
Rear Axle, kg		715
Towing Capacity, kg		1,370
<b>TYRES</b>		
R1 AG	– Front	–
	– Rear	–
R1 AG	– Front	–
	– Rear	–
R3 TURF	– Front	18 × 8.5 – 10 4PR
	– Rear	26 × 12 – 12 4PR
R3 TURF Special	– Front	–
	– Rear	–
R3 TURF Radial	– Front	–
	– Rear	–
R4 Industrial	– Front	18 × 8.5 – 10 4PR
	– Rear	26 × 12 – 12 4PR
R4 Industrial	– Front	–
	– Rear	–

\* Please note the maximum speed of the tractor may be reduced or increased by the choice of tyre. Your dealer can advise you on the correct choice, suited to your requirements and application.