

## SPECIFICATIONS

	F310R	F350R	324A	328A	331	R870R	R950R	R990R
	Front mounted			Rear mounted				
<b>RECOMMENDED TRACTOR PTO POWER*</b>								
Power	76 kW (100 hp)	91 kW (120 hp)	52 kW (70 hp)	61 kW (82 hp)	76 kW (100 hp)	155 kW (210 hp)	170 kW (230 hp)	185 kW (250 hp)
<b>CUTTERBAR</b>								
Number of discs	7	8	6	7	8	2 x 7	2 x 8	
Bolted knives reversible and retractable	-		■	■	■	-		
Quick knives change reversible and retractable	■	■	■	■	■	■	■	■
Cutting width	3.10 m	3.50 m	2.40 m	2.80 m	3.10 m	8.30 to 8.70 m	9.10 to 9.50 m	9.50 to 9.90 m
Front /rear cutting overlap	-					0.30 to 0.50 m		
Cutting height – Classic cutterbar	-		30 to 80 mm			-		
Cutting height – Quick Knives Exchange Cutterbar	35 to 85 mm		34 to 84 mm			35 to 85 mm		
<b>CONDITIONER (IMPELLER)</b>								
Tines	Mobile preloaded I-shape steel		Mobile V-shape steel			Mobile preloaded I-shape steel		
Number of tines	4 in V + 76 straights	4 in V + 100 straights	42	48	54	2 x (4 in V + 76 straights)		
Orbit diameter of tines	540 mm		510 mm			540 mm		
Rotor speed	1,000 or 755 rpm		888 or 615 rpm			1,000 or 755 rpm		
Drive	Gearbox		Belt			Gearbox		
Conditioning hood opening	10 to 50 mm		10 to 100 mm			10 to 50 mm		
<b>CONDITIONER (ROLLS)</b>								
Rolls profile	Losange	-	Chevron	-	-	Losange	-	-
Rolls diameter	240 mm	-	200 mm	-	-	240 mm	-	-
Rolls speed	1,000 rpm	-	1,000 rpm	-	-	1,000 rpm	-	-
Conditioning rolls pressure	Adjustable	-	Adjustable	-	-	Adjustable	-	-
Drive	Drive Line	-	3 Belts	-	-	Drive Line	-	-
<b>WINDROWING</b>								
Windrow width	1.20 to 2.40 m		0.90 to 1.80 m	1.00 to 2.20 m	1.20 to 2.50 m	1.30 to 3.20 m		
<b>WIDE SPREAD</b>								
Availability	-		■	■	■	■	■	■
<b>SUSPENSION</b>								
Type	Adjustable hydro-pneumatic							
<b>DIMENSIONS</b>								
Width (transport)	2.99 m	3.48 m	Below 2.50 m			2.95 m	3 m	3.35 m
Weight impeller models	1,270 kg	1,350 kg	1,000 kg	1,069 kg	1,145 kg	3,030 kg	3,211 kg	3,260 kg
Weight rolls models	-		1,050 kg	1,125 kg	-			
<b>POWERLINE</b>								
PTO speed	1,000 rpm		540 rpm		1,000 rpm			
PTO drive	Clockwise and anticlockwise		Clockwise					
Protection	Slip clutch + free wheel							
<b>REQUIRED TRACTOR EQUIPMENT</b>								
Hydraulic and electrical connections	1 S.A outlet		1 D.A outlet + 1 electrical 7 connectors			2 D.A outlet + 1 S.A+, 1 electrical 7 connectors		
Tractor hook up	Front hitch cat. 2		Rear 3 point hitch cat. 2			Cat 3 or 4N comp. Quick hitch 3/4N		

■ Available – Not available

\*The tractor requirements listed above are recommendations. Power requirement and windrows width may vary from crop and field conditions. Power indicated for rear wide cut, R870R, R950R and R990R include front moco.

	S310R	S350R	C310R	C350R
	Side pull		Centre pivot	
<b>RECOMMENDED TRACTOR PTO POWER*</b>				
Power	55 kW (75 hp)	62 kW (84 hp)	60 kW (82 hp)	70 kW (94 hp)
<b>CUT TERBAR</b>				
Number of discs	7	8	7	8
Bolted knives reversible and retractable	■	■	■	■
Quick knives change reversible and retractable	-	-	-	-
Cutting width	3.10 m	3.50 m	3.10 m	3.50 m
Cutting height	35 to 65 mm			
<b>CONDITIONER (IMPELLER)</b>				
Tines	V-shape. Preloaded			
Number of tines	88	104	88	104
Orbit diameter of tines	540 mm			
Rotor speed	780/1,000 rpm			
Drive	Gearbox			
Conditioning hood opening	8 to 50 mm			
<b>CONDITIONER (ROLLS)</b>				
Rolls material – profile	-		Profile in W pattern	
Rolls Diameter	240			
Rolls speed	800	-	800	-
Conditioning rolls pressure	Adjustable by screw	-	Adjustable by screw	-
Drive	Gearbox	-	Gearbox	-
<b>WINDROWING</b>				
Windrow width	0.9 to 2.3 m	1.10 to 2.70 m	0.9 to 2.3 m	1.10 to 2.70 m
<b>WIDE SPREAD</b>				
Availability with	Impeller			
<b>SUSPENSION</b>				
Type	Adjustable springs			
<b>DIMENSIONS</b>				
Width (transport)	3.00 m	3.50 m	3.00 m	3.50 m
Weight impeller models	2,160 kg	2,390 kg		2,540 kg
Weight rolls models	2,260 kg	-	2,500 kg	-
Length (transport)	5.7 m	5.7 m	6.8 m	6.8 m
<b>TYRES</b>				
Size	380/55x17	380/55x18	400/60x15.5	400/60x15.5
<b>POWERLINE</b>				
Tractor hook up draft links with hooks cat 3N4N	■	■	■	■
Protection	Friction clutch			
PTO speed	1,000 rpm			
<b>REQUIRED TRACTOR EQUIPMENT</b>				
Hydraulic connections, 1 double + 1 single acting outlet	■	■	■	■
Width in transport	Within moco width			