

INTRODUCING HELIXXTM 265 LITRE STAINLESS STEEL HOPPER SPREADER

APPLY CONSISTENT, CONTROLLED MATERIAL DELIVERY TO SMALLER AREAS WITH THE **HELIXX 12145 265 LITRE STAINLESS STEEL HOPPER SPREADER**. THE **12145** MODEL IS BUILT WITH MANY OF THE SAME FEATURES AS THE LARGER **HELIXX** HOPPERS AND IS DESIGNED TO FIT UTVS AND COMPACT TRUCKS.

SNOWEN

SNOVEX THE LEADER IN **SNOVEX** SNOW & ICE CONTROL

SNOWEX/



HELIXX UTV BED SPREADER (12145)

HELIXX MATERIAL DELIVERY

(Patent Pending)

The corkscrew, or "helix," design of the **HELIXX** material delivery system is optimized for efficient and cost-effective use of salt, and was designed to operate in the target range for salt spreading best practices. Its innovative design helps prevent clogs and provides a superior material flow to traditional augers.

MATERIAL COMPATIBILITY

- BULK ROCK SALT
- 🧹 50/50 SALT/SAND MIX*
- 🖌 DRY FREE-FLOWING SAND*
- BAGGED ICE MELTERS
- 🖌 HIGH END FLAKE/PELLET MATERIALS

*Optional inverted V and vibrator kits are recommended for materials that are susceptible to compacting.

🚺 FEATURES AND BENEFITS







🖌 STAINLESS STEEL

Hopper and frame are constructed of corrosion-resistant stainless steel. The frame features a unique leg and sill design to form a ridged backbone structure for greater durability, and riveted construction provides consistent, quality joints.



Baffles within the chute direct material to key areas on the spinner resulting in a remarkably even and consistent spread pattern, as well as reducing material directed back at the vehicle.

ACCESSORY INTEGRATION

Conveniently connect accessories directly into the hub mounted in the back of the hopper. Accessories automatically integrate with the hopper control without having to run additional wires from the front of the vehicle.



FULL LENGTH HELIXX SYSTEM

The **HELIXX** system runs the entire length of the hopper with variable flights, promoting even unloading of material.





FLIP-UP/REMOVABLE CHUTE

Remove a single pin to flip-up the chute for easy access to the hitch and clean out. The chute can be completely removed with just two pins.

DUAL VARIABLE-SPEED CONTROL

Allows for variable control of spinner and **HELIXX** system speeds for precise material delivery, whether at low or high output. Features no-blast startup, auto reverse and integrates with accessories.

SPECIFICATIONS 12145

Capacity (Volume)
Capacity (Weight)
Empty Weight
Hopper Length
Min. Bed Length Required
Spread Width

340kg 87kg 762mm 734mm 9m

268 litres

ACCESSORIES INCLUDE:

Attached to structural cross member, it vibrates the entire unit to maximize flow of bulk materials.





SCAN HERE

TO SEE A DEMO

TRY IT FOR YOURSELF! CALL US TO BOOK YOUR FREE DEMO TODAY! Call: 01264 345878 *www.wessexintl.com*

