



SIDEWINDER
EXTENSION CONVEYOR

BFR-180
ROUND BALE FEEDER

CROSSFIRE
BEDDER ATTACHMENT

KEY FEATURES & BENEFITS

- ✓ **FEED ROUND BALES** – Save up to 20% on feed bills
- ✓ **SPREADS WITHOUT CHOPPING** – Minimal dust and projectiles
- ✓ **UTILISE 1 MACHINE FOR 2 OPERATIONS** – Save time and money
- ✓ **BED UP TO 10 METRES** – Great bedding distribution
- ✓ **FITS TO LOADERS & TRACTORS** – Suits many applications
- ✓ **NO ELECTRONICS** – Simple to use and maintain detachable loading headstock
- ✓ **WITH QUICKLATCH™ SYSTEM** – Fast and easy reloading

SPECIFICATIONS

	BFR-180 & OPTIONS
Round bale size	Up to 6'x5' (1.2x1.2m or 1.8x1.5m)
Round bale weight	Up to 1,000kg
Unit weight (BFR-180 only)	770kg
Unit weight (with Crossfire only)	1,000kg
Unit weight (with Sidewinder only)	1,050kg est
Unit weight (with Crossfire & Sidewinder)	1,280kg est
Hydraulics required	1x double acting for BFR-180 & Crossfire, 2x double acting for Sidewinder
Oil flow	12 litres/min (BFR-180 only), 50 litres/min (Crossfire & Sidewinder)

3 STAGE LATCHING SYSTEM ... It's as simple as 1,2,3



- 1**
- ✓ **LIFT LATCH**
 - ✓ **DRIVE BACKWARDS TO DISENGAGE HEADSTOCK**
 - ✓ **SPIKE BALE**

- 2**
- ✓ **PLACE BALE OVER CRADLE**
 - ✓ **REMOVE WRAP**
 - ✓ **LOWER BALE ONTO CRADLE**

- 3**
- ✓ **LOCATE TINE CUPS**
 - ✓ **DRIVE FORWARD TO ENGAGE HEADSTOCK**
 - ✓ **HYDRAULIC DRIVE AND SAFETY CATCH AUTO ENGAGES**
 - ✓ **LIFT AND COMPLETE**

Designed and manufactured in our Hampshire UK factory, the Wessex **BFR-180** (patent pending) is a modular feeding and bedding system that can be configured as a bale feeder (**MODE 1**), a bale feeder with an extension chute (**MODE 3**), or a straw spreader and bale feeder combination (**MODE 2**).

The **BFR-180** only requires one tractor or telehandler to operate, and the maintenance is very low with only four grease points and no electrics!

VISIT THE WEBSITE OR CALL US TO BOOK YOUR DEMO TODAY.

BFR-180 ROUND BALE FEEDER

As a bale feeder, it can feed round bales of hay, haylage, straw and silage from either side with ease. Featuring massive 5,500kg rated roller chains with galvanized crossbars and a high spec Danfoss hydraulic motor, the **BFR-180** is a very reliable, seriously durable bale feeder that is simple to use and very easy to maintain.

- ✓ **REQUIRES ONE DOUBLE ACTING HYDRAULIC SPOOL**



BFR-180 ROUND BALE FEEDER & CROSSFIRE STRAW SPREADER

With the innovative **CROSSFIRE** straw spreader attached, bedding and feeding tasks can be undertaken with the same machine, bed from one side and feed off the other.

The Wessex **CROSSFIRE** straw spreader is unlike conventional straw choppers as it spreads the straw in its baled length, with minimal dust and projectiles, and up to ten metres. Straw choppers are renowned for creating excessive dust, which in an enclosed environment can be a serious threat to the health of the stock. Chopping bedding straw also reduces its effective life span within the bedding area.

- ✓ **REQUIRES ONE DOUBLE ACTING HYDRAULIC SPOOL**



BFR-180 ROUND BALE FEEDER & SIDEWINDER EXTENTION

The Wessex **SIDEWINDER** is an extension conveyor that attaches to the **BFR-180** for high level feeding into a trough or manger. The Sidewinder extends to the left leaving the right free to feed or alternatively bed with the **CROSSFIRE** straw spreader attached.

- ✓ **REQUIRES TWO DOUBLE ACTING HYDRAULIC SPOOLS, OR ONE DOUBLE ACTING WITH DIVERTER VALVE**



...OR A COMBINATION OF ALL 3 MODES

Feed into a trough or manger and bed straw with the same machine.

- ✓ **REQUIRES TWO DOUBLE ACTING HYDRAULIC SPOOLS, OR ONE DOUBLE ACTING WITH DIVERTER VALVE**

