

R732i

Key Specs

Solution tank nominal volume - 3200.0 L

Solution tank actual volume (+ 5%) - 3360.0 L

Tank material - Polyethylene

Rinse water tank volume - 400.0 L

Tank level indicator - Dry level indication with float Digital tank level indication

Tanks

Solution tank nominal volume - 3200.0 L

Solution tank actual volume (+ 5%) - 3360.0 L

Tank material - Polyethylene

Rinse water tank volume - 400.0 L

Tank level indicator - Dry level indication with float Digital tank level indication

Pumps

Pump - Centrifugal spray pump (at 3 bar [43.5 psi]): 750 L/min 198.1 gpm Centrifugal fast fill pump (self-priming): 600 L/min 158.5 gpm

Solution pump drive - Load sense hydraulic pump drive for spray system with PowrSpray™ system

Size filling hose connection - 51.0 mm

Central operation station control

Solution system type - PowrSpray

Valve control - Electric operated valves

Automatic filling - Base

Central operation station control

Automatic agitation control - Base – on/off and intensity control based on tank volume

Automatic dilution and rinsing - AutoDilute: stepwise dilution and continuous dilution Boom rinse, system rinse, and rinse cycles

Spray booms/section setup/meter

Double-folded boom – 2.55-m (8.4-ft) transport width - 24.0 m

Triple-folded boom – 3-m (9.8-ft) transport width - 27.0 m

Nozzle body - Five-way nozzle holder

Spray line system - Base: Pressure circulation spray system (no section valves, nozzles opened with air shutoff valves)

Spray boom positioning, stabilization system

Horizontal sprayboom stabilization system - Base: Center frame with pendulum with shock absorbers Optional: Boom suspension kit for spraying hilly fields

Vertical boom suspension system to prevent boom yawing - Base: Center frame with hinge point with shock absorbers and polyurethane dampers Optional: Independent yaw suspension and damping (push rod system)

Boom tilt control - Hydraulic boom tilt cylinder

Automatic boom leveling - Optional John Deere TerrainControl™ Pro: John Deere TerrainCommand™ Pro:

Variable geometry adjustment - Optional degree (angle)

Machine control hydraulics

Hydraulic control type - Base: Electrohydraulic boom folding

Machine control - Base: ISOBUS

Automatic rate controller

Power supply - ISOBUS connector (with optional ISOBUS control) V

Rate control - Automatic rate control with pressure-and-flow sensor

Section control/machine operation - GNSS section control ready

Individual nozzle control - Optional

Tractor connection

Linkage to tractor - Lower linkage: Fixed drawbar or track-following drawbar Upper linkage: Fixed drawbar or track-following drawbar

Ball coupling type - K-80 or K-80 with RD-40 eye for harbor transport

Ring tow eye type - 40.0 mm

Steering system

Type - Optional: Steering drawbar

Axle and wheels

Axle suspension - Double-linked axle suspension Optional double-linked axle suspension on Select and Premium editions

Rims - Fully welded

Bolt pattern - 10 bolts

Row-crop tires - 270/95R48 Factory choice brand (minimum 144A8/140B) 300/95R46 Factory choice brand (minimum 148A8/144B) 340/85R48 Factory choice brand (minimum 152A8/152B)

Flotation tires - 420/85R38 Factory choice brand (minimum 144A8/141B) 480/70R38 Factory choice brand (minimum 145A8/142B) 520/70R38 Factory choice brand (minimum 150A8/147B) 520/85R38 Factory choice brand (minimum 155A8/152B)

Speed (depends on local legal requirements) - 25.0 km/h

Brakes - Base: Single line hydraulic brakes with parking brake Optional: Dual line air brakes with parking brake

Fixed axle available track widths - Minimum - 150.0 cm

Fixed axle available track widths - Maximum - 225.0 cm

Sliding axle available track widths - Minimum - 150.0 cm

Sliding axle available track widths - Maximum - 210.0 cm

Fenders - 400.0 mm

Accessories

Clothing locker - Base

Chemical storage box - Optional: Chemical storage box with lock function

Transfer valve - Optional

Eductor station light - Optional

Boom working lights - Optional: Halogen or light-emitting diode (LED) field lighting kit

Extremity nozzle holder - Left-side mounted and/or right-side mounted (option) Electric or pneumatic operation Both edge nozzle and off-center nozzle functionality

Closed chemical transfer ready connection - Optional

Hydraulic system oil filter - Optional

Self-cleaning pressure filter - Optional

Beacon light - Optional

Additional Information

Date collected - 2021-06-03T17:03:00