

T6 700

Key Specs

Rated Power - 270.0 kW

Fuel Capacity - 800.0 L

Threshing Cylinder Diameter - 66.0 cm

Concave Area - 1.35 3¡

Separating Area - 4.0 3¡

Total Cleaning Area (Louvered) - 4.9 3¡

Grain Tank Size - 11000.0 L

Peak Unloading Rate - 150.0 L/s

Engine

Rated Speed - 2200.0 rpm

Rated Power - 270.0 kW

Power Boost @ Rated Speed - 25.0 kW

Fuel Capacity - 800.0 L

Feeding

Length - 185.0 cm

Threshing/ Separating

Separator Drum Diameter - 80.0 cm

Separator Drum Speed - Minimum - 380.0 rpm

Separator Drum Speed - Maximum - 760.0 rpm

Threshing/ Separating

Threshing Cylinder Speed - Minimum - 450.0 rpm
Threshing Cylinder Speed - Maximum - 990.0 rpm
Threshing Cylinder Diameter - 66.0 cm
Concave Area - 1.35 3¡
Separating Area - 4.0 3¡

Cleaning System

Chaffer - 2.63 3¡
Sieve Area - 2.27 3¡
Total Cleaning Area (Louvered) - 4.9 3¡
Cleaning Fan Speed - Maximum - 1350 rpm
Cleaning Fan Speed - Minimum - 550 rpm

Grain Handling

Grain Tank Size - 11000.0 L
Unloading Auger Length - 5.6 m
Peak Unloading Rate - 150.0 L/s

Additional Information

Date Collected - 2024-06-28T16:53:00