

# 750A (6.0 Meter)

## Key Specs

| |
|---|
| Working Width - 6.0 m |
| Height With Wings Folded - 4.0 m |
| Transport Wheels And Tires - Four wheels - 31x13.5x15 8PR or 31x15.5x15 8PR |
| Brake System - Hydraulic or pneumatic |

## Dimensions / Capacities

| |
|---|
| Working Width - 6.0 m |
| Height With Wings Folded - 4.0 m |
| Total Weight - 6800.0 kg |
| Hitch Weight - 2600.0 kg |
| Transport Width - 3.0 m |
| Seed Hopper Volume - 2300.0 L |
| Suggested Fan Speed For Normal Seeds - 4200 rpm |
| Transport Wheels And Tires - Four wheels - 31x13.5x15 8PR or 31x15.5x15 8PR |

## Openers

| |
|---|
| Row Spacing - 166.0 mm |
| Number Of Openers - 18 |
| Seeding Depth - 13 to 89 mm (0.5 to 3.5 in.) in 6.35-mm (0.25-in.) increments |

## Hydraulics

| |
|---|
| Active Hydraulic Down Pressure - 4800 kPa (48 bar; 696.2 psi) |

## Hydraulics

| |
|---|
| Working Pressure - 20680 kPa |
| Burst Pressure - 82740 kPa |
| Down Pressure - Hydraulically adjustable, depending on soil conditions |

## Machine Configuration

| |
|---|
| Brake System - Hydraulic or pneumatic |
| Marker Arms (Optional) - Hydraulically actuated |